

2,5 kW

3,5 kW

4,2 kW



Standard YR-HQS01

NEW CONSOLE



Silence



Double Flow



Sleep



Wi-Fi control integrated



R32 Detector

- Low noise level
- Double airflow
- Compact design

- Sleep function for greater night time comfort
- Wi-Fi control integrated
- R32 Detector

Indoor Unit	Model		AF25S2SD1FA(D)	AF35S2SD1FA(D)	AF42S2SD1FA(D)
Performance data					
Output power - COOLING	nom (min-max)	kW	2,50	3,40	4,20
Output power - HEATING	nom (min-max)	kW	3,00	3,50	4,70
Power supply		Ph/V/Hz	1/220~240/50/60	1/220~240/50/60	1/220~240/50/60
Treated air volume	(H/M/L/Q)	m ³ /h	450/400/350/300/250	500/450/400/350/300	580/530/480/430/380
Indoor Unit					
High sound power		dB	52	55	58
Sound pressure		dB(A)	40/32/25/20	42/34/26/21	46/37/33/28
Net dimensions	WxDxH	mm	700x210x600	700x210x600	700x210x600
Packaging dimensions	WxDxH	mm	783x303x695	783x303x695	783x303x695
Net/gross weight		kg	16,5/18,5	16,5/18,5	16,5/18,5
Installation data					
Liquid pipe	∅	mm (inch)	6,35 (1/4)	6,35 (1/4)	6,35 (1/4)
Gas pipe	∅	mm (inch)	9,52 (3/8)	9,52 (3/8)	9,52 (3/8)

AF25 - AF35 - AF42

