

# Residential Multisplit Inverter CEILING FLOOR

# Haier

3.5 kW

5.0 kW

7.1 kW

OPTIONAL CONTROL



Silence



Flow +



5 Speed



Fresh Air



On-Off Card

- Low noise level
- Flow +: Internal deflectors are divided into two groups with independent motors (independent right-left airflow)
- 5 fan speed: turbo, high, medium, low, super low (only with YR-HBS01 or wired controller)
- 'Fresh air' knockout is incorporated in the chassis to allow fresh air introduction of up to 20% of nominal unit air flow without compromising the cooling capacity. More than 20% of the air conditioner's thermal cooling capacity is penalised.

INDOOR UNIT	Model		AC35S2SG1FA	AC50S2SG1FA	AC71S2SG1FA
<b>Performance data</b>					
Output power - COOLING	nom (min-max)	kW	3.5	5.0	7.1
Output power - HEATING	nom (min-max)	kW	4.0	5.8	8.0
Power supply		Ph/V/Hz	1/220-240/50	1/220-240/50	1/220-240/50
Treated air volume	Hi / Mi / Lo	m <sup>3</sup> /h	750/620/500/400	880/750/650/500	1250/1128/930/840
<b>Indoor Unit</b>					
Sound power - COOLING		dB	53	57	62
Sound pressure - COOLING		dB(A)	39/36/33	44/41/38	41/38/36/33
Dimensions	WxDxH	mm	1000x230x680	1000x230x680	1325x230x680
Net weight		Kg	26	26	26
<b>Installation data</b>					
Liquid pipe	∅	mm	6.35	6.35	9.52
Gas pipe	∅	mm	9.52	12.7	15.88

AC35 - AC50 - AC71

