

MRV INDOOR UNIT Floor Console, exposed type, double flow



AF052MBERA
AF072MBERA
AF092MBERA
AF122MBERA
AF162MBERA
AF182MBERA



Optional controller
HW-BA116ABK



Optional controller
HW-BA101ABT



Optional controller
YR-E17A



Optional remote control
YR-HD01



Optional controller
YR-E16B

- Double air delivery, upper and lower.
In heating mode: both outputs are enabled, to spread hot air at floor level preventing the "cold feet" effect typical of only higher deliveries. By acting on the on-board selector it is possible to inhibit the lower output in heating mode.
In cooling mode: The unit works only with the top delivery, the lower output automatically closes.
- Compact and elegant design
- Silent operation
- DC inverter fan motor
- 5 fan speeds only selectable with wired controller YR-E16B and YR-E17A.

Model		AF052MBERA	AF072MBERA	AF092MBERA	AF122MBERA	AF162MBERA	AF182MBERA
Capacity							
Cooling	kW	1.5	2.2	2.8	3.6	4.5	5.0
Heating	kW	1.7	2.6	3.2	4	5	5.5
Electrical Parameters							
Power supply	Ph-V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
Ventilation							
Air flow (High)	m ³ /h	460/380/300	460/380/300	460/380/300	510/450/350	640/470/390	640/470/390
Sound pressure level (H/m/l)	dB(A)	42/36/31	42/36/31	43/39/35	43/39/35	48/44/38	48/44/38
Sound power level (H/m/l)	dB(A)	53/47/42	53/47/42	54/50/46	54/50/46	59/55/49	59/55/49
Installation – Dimensions							
Unit Dimensions WxDxH	mm	700x210x600	700x210x600	700x210x600	700x210x600	700x210x600	700x210x600
Packaged unit dimensions WxDxH	mm	783x303x695	783x303x695	783x303x695	783x303x695	783x303x695	783x303x695
Net weight / Gross weight	Kg	17/19	17/19	17/19	17/19	17/19	17/19
Ø Liquid side refrigerant pipe	mm	6.35	6.35	6.35	6.35	6.35	6.35
Ø Gas side refrigerant pipe	mm	12.7	12.7	12.7	12.7	12.7	12.7

